

Aluminum Sulfate, Solid



SDS No. 010
3-Mar-2015

Safety Data Sheet

1. IDENTIFICATION

Product Identifier

Product Name Aluminum Sulfate

Manufacturer

USALCO, LLC
2601 Cannery Ave
Baltimore, MD 21226

Other means of identification

SDS # 010

Recommended use of the chemical and restrictions on use

Recommended Use Water treatment chemical

Emergency Telephone Number

Company Phone Number 410-918-2230

Emergency Telephone (24 hr) 800-282-5322

2. HAZARDS IDENTIFICATION

Appearance White granules or powder

Physical State Solid

Odor Negligible

Classification

Acute toxicity - Oral
Eye Damage/Irritation

Category 4
Category 2B

Signal Word

Warning

Hazard Statements

-Causes serious eye irritation
-Harmful if swallowed

Precautionary Statements – Prevention

-Wear eye/face protection. Wash hands and any exposed skin thoroughly after handling.
-Wear protective gloves.
-Avoid breathing dust.

Precautionary Statements - Response

-IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical attention.
-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention.
-IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.

Precautionary Statements – Disposal

Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, State, and local regulations.



Aluminum Sulfate, Solid

SDS No. 010

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Aluminum Sulfate	10043-01-3	100

4. FIRST-AID MEASURES

First Aid Measures

General Advice	After first aid, get appropriate in-plant, paramedic, or community medical support.
Eye Contact	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Skin Contact	Wash off immediately with plenty of water. Take off contaminated clothing. Wash contaminated clothing before reuse.
Inhalation	Remove to fresh air.
Ingestion	Rinse mouth. Do not induce vomiting. Get medical attention if there are symptoms.

Most important symptoms and effects

Symptoms	May cause eye burns and permanent eye damage. Contact may cause irritation and redness. Irritating to mouth, throat, and stomach if ingested. Vomiting. May cause shortness of breath, nausea, dizziness, and headache. May cause irritation to the mucous membranes and upper respiratory tract.
----------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
--------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Aluminum Sulfate will not burn.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

If exposed to temperatures greater than 1400°F, Aluminum Sulfate will decompose generating toxic and corrosive gas.

Hazardous Combustion Products Oxides of sulfur.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Do not release runoff from fire control methods to sewers or waterways.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Use personal protective equipment as required. Ventilate affected area.
Other Information	Aluminum Sulfate may absorb moisture, and powders or crystals can solidify into a single mass.
Environmental Precautions	Do not discharge wastewaters to the environment or a wastewater treatment plant without authorization from the appropriate officials.

Aluminum Sulfate, Solid

SDS No. 010

Methods and material for containment and clean up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Clean-Up	Sweep up and shovel into suitable containers for disposal. Flush residue with water. Neutralize with soda ash or lime if necessary. Aluminum Sulfate solutions can have a pH less than two. The neutralization of aluminum sulfate can generate carbon dioxide.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling	Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use personal protection recommended in Section 8. Minimize dust generation and accumulation. Avoid moisture contamination.
-------------------------	--

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Wet aluminum sulfate will corrode steel.
Incompatible Materials	Alkalis. Water-reactive materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

No exposure limits noted for product.
Exposure Limits for aluminum metal
NIOSH REL - TWA 10 mg/m3 (total) TWA 5 mg/m3 (resp)
OSHA PEL - TWA 15 mg/m3 (total) TWA 5 mg/m3 (resp)

Appropriate engineering controls

Engineering Controls	Showers. Eyewash stations. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of the chemical release. Dust emission control may be required depending on the dust generation rate. Isolation operations can also reduce exposure.
----------------------	---

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye & face protection regulations in 29 CFR 1910.133 or European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with, contact lenses.
Skin and Body Protection	Wear appropriate clothing to prevent repeated or prolonged skin contact.
Respiratory Protection	Seek professional advice prior to respirator selection and use. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.
General Hygiene Considerations	Do not eat, drink or smoke when using this product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Aluminum Sulfate, Solid

SDS No. 010

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Solid, white granules or powder
Odor	None
Odor threshold	Not relevant
pH	3.3 ± 0.5 (1% solution)
Density	<98 lb/cu ft
Melting point/freezing point	105° C / 221° F
Initial boiling point and boiling range	Not relevant
Decomposition temperature	±1,400° F
Viscosity	Not relevant
Auto-ignition temperature	Not flammable
Evaporation rate;	Will not evaporate
Flammability (solid, gas)	Not flammable
Flash point	Will not burn
Upper/lower flammability or explosive limits	Will not burn
Partition coefficient: n-octanol/water	Not relevant
Solubility	Soluble in water
Vapor density	None
Vapor pressure	None

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

Contact with incompatible materials causes exothermic reactions.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Contact with incompatible materials.

Incompatible Materials

Alkalis. Water-reactive materials.

Hazardous Decomposition Products

Thermal oxidative decomposition of Aluminum Sulfate occurs at temperatures greater than 1400°F and can produce sulfur oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Causes serious eye damage.
Skin Contact	Avoid contact with skin.
Inhalation	Avoid inhalation of dust.
Ingestion	Harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Aluminum Sulfate 10043-01-3	= 1930 mg/kg (Rat)	-	-

Aluminum Sulfate, Solid

SDS No. 010

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Aluminum Sulfate 10043-01-3		100: 96 h Carassius auratus mg/L LC50 37: 96 h Gambusia affinis mg/L LC50 static		136: 15 min Daphnia magna mg/L EC50

Persistence/Degradability

Not determined

Bioaccumulation

Not determined

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Waste Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN3077 if shipped in a single container with a weight greater than the RQ, 5,000 lbs.
Proper Shipping Name Environmentally hazardous substance, solid, n.o.s. (Aluminum Sulfate)
Hazard Class 9
Packing Group III
Reportable Quantity (RQ) 5000 lbs

IATA

Not regulated

IMDG

Marine Pollutant This material may meet the definition of a marine pollutant

Aluminum Sulfate, Solid

SDS No. 010

15. REGULATORY INFORMATION

International Inventories

Not determined

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Aluminum Sulfate 10043-01-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Not listed.

CWA (Clean Water Act)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Aluminum Sulfate 10043-01-3	5000 lb			X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	1	0	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	1	0	0	Not determined

Issue Date 30-Apr-2013
Revision Date: 3/9/2015
Revision Note New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Univar USA Inc Safety Data Sheet

For Additional Information contact SDS Coordinator during business hours, Pacific time: (425) 889-3400

Notice

Univar USA Inc. ("Univar") expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this SDS as a product specification. For product specification information refer to a product specification sheet and/or a certificate of analysis. These can be obtained from your local Univar sales office.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Univar makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Univar's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process